

Water Baths | Economy Type

BM302-E/312-D

Made in Japan

Temp. control range RT+ +10~90°C

Large 5 L bath with an internal diameter of $\Phi 240$ mm.

Features

- The flat design, with no heater or sensor inside the bath, makes cleaning easy.
- Equipped with comprehensive safety features, including automatic overheat protection, an upper temperature limit, and independent overheat protection.



Specifications

	BM302-E	BM312-D
Operating temp. range	Room temp. +10 to 90°C	
Temp. adjustment accuracy	±1.0°C	
Temp. control system	PID control by microprocessor	
Temp. setting/display method	White LED digital display, key entry, minimum digit of 1°C	
Heater	1kW	
Safety device	Automatic overheat prevention, independent overheat prevention (fixed temp.)	
Additional function	Overshoot alert, auto-resume(selectable), Calibration offset	
External dimensions ($\Phi \times H$ mm)	$\Phi 262 \times 240$ mm	
Remarks (dimensions)	Bath internal capacity : Approx. 5L	
Power supply *	AC100 to 115V 10 to 12A (50/60Hz) Service outlet 2A excluded	AC200 to 230V 5 to 6A (50/60Hz) Service outlet for RE212 : None
Weight	4.5kg	

* Voltage modifications other than the listed specifications are also available. Please contact us for details.

- Sterilizers 1
- Granulation and Spray Dryers 2
- Furnaces 3
- Ovens 4
- Incubators 5
- Plasma Equipment 6
- Water Purifiers 7
- Baths 8**
- Water Circulators 9
- Rotary Evaporators 10
- Stirrers & Shakers 11
- Options 12